

MOTIP Bi-Chromatage Spray

Ord.-no.: 07305

Technical Information



Fast drying bi-chromatage spray with good coverage for professional use. To repair minor damage in surfaces of gold chromed steel. Bi-chromatage spray has good surface hardness and is non-fading and UV-resistant. MOTIP Bi-Chromatage Spray is resistant to petrol, chemicals and weather influences and is wear resistant and scratch free.

Quality & properties

- Fast drying
- Excellent coverage and adhesion
- Non-fading and UV resistant
- Good surface hardness
- Resistant to petrol, chemicals and weather influences
- Wear resistant and scratch free

Physical & chemical data

- Colourname: gold
- Degree of gloss: mat, 10 ±2
- Vapour pressure: 3500/20 bar
- Storage stability: 10 y
- Content: 500 ML

How to use

- Before use, carefully read the directions on the packaging and act accordingly.
- The surface should be clean, dry and free of grease.
- The aerosol should have room temperature. Best processing temperature 15 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimetre.
- Apply the bi-chromatage spray in several thin layers. Before applying the next layer, again shake the aerosol.
- After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).
- The drying time depends on the ambient temperature, the humidity of the air and the thickness of the lacquer applied.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

For any further technical questions call our hotline +31 (0) 561 69 44 00 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

As of June 9, 2022 – This release replaces all eventually earlier issued versions.