

MOTIP Quick Start

Ord.-no.: 090405, 290405

Technical Information



Use MOTIP Quick Start for eliminating internal combustion engine starting problems of both petrol and diesel engines. The spray is ether-based.

Quality & properties

- Fast-acting
- Ether-based
- Misty spray pattern

Physical & chemical data

- Base: Diethylether with mineral oil
- Colourname:
 - ◊ no colour
 - ◊ transparent
- Smell: Characteristic
- Surfaces: Diesel engines, Petrol engines
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Spray rate: 1,70
- Vapour pressure: 3500/20 bar
- Relative density: 0.711 g/ml
- Storage stability: 10 y
- Content:
 - ◊ 500 ML
 - ◊ 200 ML

How to use

- Before use, carefully read the directions on the packaging and act accordingly.
- The aerosol should have room temperature.
- Before use, shake the aerosol.
- Inject quick start into the air inlet of the air filter for several seconds.
- Start the engine.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labeling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

For any further technical questions call our hotline +31 (0) 561 69 44 00 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

As of June 10, 2022 – This release replaces all eventually earlier issued versions.