

MOTIP Electro Protect

Ord.-no.: 090108, 290108

Technical Information



Prevent starting problems caused by moisture in electrical systems with MOTIP Electro Protect. Electro Protect is water- and moisture-repellent. It is also resistant to salt, weak acids, bases and is pH neutral. MOTIP Electro Protect offers excellent adhesion and corrosion protection.

Quality & properties

- Good penetrating properties
- Moisture- and water repellent
- Excellent corrosion prevention
- Resistant to water, salt and weak acids and bases
- Excellent adhesion

Physical & chemical data

- Base: Mineral oil
- Colourname:
 - ◊ no colour
 - ◊ transparent
- Smell: Characteristic
- Surfaces: Switches, Spark Plugs, Batteries, Printed Circuit Board Switches, Multiple sockets, Distributor caps, Cables, Fuses, Electric tools, Current distributors, Plugs, Electric systems (which should be protected for moisture)
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Spray rate: 1,9
- Vapour pressure: 3500/20 bar
- Relative density: 0.802 g/ml
- Storage stability: 10 y
- Content:
 - ◊ 500 ML
 - ◊ 200 ML

How to use

- Before use, carefully read the directions on the packaging and act accordingly.
- The aerosol should have room temperature
- Best processing temperature 10 to 25°C.
- Before use, shake the aerosol.
- Switch off electrical installations before treatment.
- The parts to be treated must be clean, dry and free of grease.
- Apply electro protect in several thin layers.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

For any further technical questions call our hotline +31 (0) 561 69 44 00 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

European Aerosols GmbH, Kurt-Vogelsang-Straße 6, 74855 Haßmersheim - info-de@european-aerosols.com
European Aerosols B.V., Wolfraamweg 2, NL-8471 XC Wolvega - info-nl@european-aerosols.com