

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.06.2022

Version number 3 (replaces version 2)

Revision: 30.03.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **MOTIP HYBRID COLORS SILVER GREY RAL 7001 400 ML**

Article number: 304711

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Product category Paint remover

Process category

PROC7 Industrial spraying

PROC11 Non industrial spraying

Application of the substance / the mixture Spray varnish

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

European Aerosols B.V.*

Wolfraamweg 2

NL-8471 XC Wolvega

The Netherlands

Tel : +31 (0)561 694400

e-mail: sds-nl@european-aerosols.com

*Formerly known as Motip Dupli B.V.

Further information obtainable from: Department Product Safety

1.4 Emergency telephone number:

+31 (0)561-694400 (09:00h - 17:00h)

UK: NPIS National Poisons Information Centre Tel: +44 0344 892 0111

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.06.2022

Version number 3 (replaces version 2)

Revision: 30.03.2022

Trade name: MOTIP HYBRID COLORS SILVER GREY RAL 7001 400 ML

(Contd. of page 1)

· Hazard pictograms

GHS02 GHS07

· Signal word *Danger***· Hazard-determining components of labelling:***1-methoxy-2-propanol**acetone**propan-2-ol**2-methoxy-1-methylethyl acetate***· Hazard statements***H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.**H319 Causes serious eye irritation.**H336 May cause drowsiness or dizziness.***· Precautionary statements***P101 If medical advice is needed, have product container or label at hand.**P102 Keep out of reach of children.**P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.**P211 Do not spray on an open flame or other ignition source.**P251 Do not pierce or burn, even after use.**P260 Do not breathe spray.**P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.**P501 Dispose of contents / container in accordance with regional regulations.***· Additional information:***Buildup of explosive mixtures possible without sufficient ventilation.**EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.***· 2.3 Other hazards****· Results of PBT and vPvB assessment****· PBT:** Not applicable.**· vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures**· Description:** Mixture of substances listed below with nonhazardous additions.**· Dangerous components:**

| | | |
|---|---|-----------|
| CAS: 115-10-6 EINECS: 204-065-8 Index number: 603-019-00-8 Reg.nr.: 01-2119472128-37 | <i>dimethyl ether</i> ⚠ Flam. Gas 1A, H220 Press. Gas (Comp.), H280 | 50-<75% |
| CAS: 107-98-2 EINECS: 203-539-1 Index number: 603-064-00-3 Reg.nr.: 01-2119457435-35 | <i>1-methoxy-2-propanol</i> ⚠ Flam. Liq. 3, H226 ⚠ STOT SE 3, H336 | 12.5-<20% |
| CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 Reg.nr.: 01-2119471330-49 | <i>acetone</i> ⚠ Flam. Liq. 2, H225 ⚠ Eye Irrit. 2, H319; STOT SE 3, H336 EUH066 | 12.5-<20% |

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.06.2022

Version number 3 (replaces version 2)

Revision: 30.03.2022

Trade name: MOTIP HYBRID COLORS SILVER GREY RAL 7001 400 ML

(Contd. of page 2)

| | | |
|---|---|---------|
| CAS: 9004-70-0 | cellulose nitrate Expl. 1.1, H201 | 2.5-<5% |
| CAS: 111-76-2 EINECS: 203-905-0 Index number: 603-014-00-0 Reg.nr.: 01-2119475108-36 | 2-butoxyethanol Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319 ATE: LD50 oral: 1200 mg/kg | 2.5-<5% |
| CAS: 13463-67-7 EINECS: 236-675-5 Index number: 022-006-00-2 Reg.nr.: 01-2119489379-17 | titanium dioxide Carc. 2, H351 | <2.5% |
| CAS: 67-63-0 EINECS: 200-661-7 Index number: 603-117-00-0 Reg.nr.: 01-2119457558-25 | propan-2-ol Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336 | <2.5% |
| CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29 | 2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226 STOT SE 3, H336 | <2.5% |

Additional information:

CAS 9004-70-0: GB CLP Note T

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures**4.1 Description of first aid measures**

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Generally the product does not irritate the skin.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures**5.1 Extinguishing media**

Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.

5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

5.3 Advice for firefighters -

Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources.

6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.**6.3 Methods and material for containment and cleaning up:**

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.06.2022

Version number 3 (replaces version 2)

Revision: 30.03.2022

Trade name: MOTIP HYBRID COLORS SILVER GREY RAL 7001 400 ML

(Contd. of page 3)

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage**· 7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.**· Information about fire - and explosion protection:**

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Keep respiratory protective device available.

· 7.2 Conditions for safe storage, including any incompatibilities**· Storage:****· Requirements to be met by storerooms and receptacles:**

Observe official regulations on storing packagings with pressurised containers.

· Information about storage in one common storage facility: Not required.**· Further information about storage conditions:** Keep container tightly sealed.**· Storage class:** 2 B**· 7.3 Specific end use(s)** No further relevant information available.**SECTION 8: Exposure controls/personal protection****· 8.1 Control parameters****· Ingredients with limit values that require monitoring at the workplace:****115-10-6 dimethyl ether**WEL Short-term value: 958 mg/m³, 500 ppmLong-term value: 766 mg/m³, 400 ppm**107-98-2 1-methoxy-2-propanol**WEL Short-term value: 560 mg/m³, 150 ppmLong-term value: 375 mg/m³, 100 ppm

Sk

67-64-1 acetoneWEL Short-term value: 3620 mg/m³, 1500 ppmLong-term value: 1210 mg/m³, 500 ppm**111-76-2 2-butoxyethanol**WEL Short-term value: 246 mg/m³, 50 ppmLong-term value: 123 mg/m³, 25 ppm

Sk, BMGV

13463-67-7 titanium dioxideWEL Long-term value: 10* 4** mg/m³

*total inhalable **respirable

67-63-0 propan-2-olWEL Short-term value: 1250 mg/m³, 500 ppmLong-term value: 999 mg/m³, 400 ppm**108-65-6 2-methoxy-1-methylethyl acetate**WEL Short-term value: 548 mg/m³, 100 ppmLong-term value: 274 mg/m³, 50 ppm

Sk

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.06.2022

Version number 3 (replaces version 2)

Revision: 30.03.2022

Trade name: MOTIP HYBRID COLORS SILVER GREY RAL 7001 400 ML

(Contd. of page 4)

· **Ingredients with biological limit values:**

111-76-2 2-butoxyethanol

BMGV 240 mmol/mol creatinine
 Medium: urine
 Sampling time: post shift
 Parameter: butoxyacetic acid

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Appropriate engineering controls** No further data; see item 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Avoid contact with the eyes.

· **Respiratory protection:**



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A2/P3

· **Hand protection**



Protective gloves

· **Material of gloves**

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· **Penetration time of glove material**

Butyl rubber gloves with a thickness of 0.4 mm are resistant to:

Acetone: 480 min

Butyl acetate: 60 min

Ethyl acetate: 170 min

Xylene: 42 min

Butyl rubber gloves with a thickness of 0.4 mm are solvent resistant for 42- 480 minutes. As protective measure, we recommend that users and responsible persons for work safety assume solvent resistance length of 42 minutes. Considering the data in section 3 of this SDS, one can assume longer resistance length in particular cases.

· **Eye/face protection**



Tightly sealed goggles

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Physical state**

Aerosol

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.06.2022

Version number 3 (replaces version 2)

Revision: 30.03.2022

Trade name: MOTIP HYBRID COLORS SILVER GREY RAL 7001 400 ML

(Contd. of page 5)

| | |
|--|--|
| · Colour: | Different according to colouring |
| · Odour: | Nearly odourless |
| · Odour threshold: | Not determined. |
| · Melting point/freezing point: | Undetermined. |
| · Boiling point or initial boiling point and boiling range | Not applicable, as aerosol. |
| · Flammability | Not applicable. |
| · Lower and upper explosion limit | |
| · Lower: | 1.9 Vol % |
| · Upper: | 26.2 Vol % |
| · Flash point: | Not applicable, as aerosol. |
| · Ignition temperature: | 240 °C (464 °F) |
| · Decomposition temperature: | Not determined. |
| · pH | Mixture is non-soluble (in water). |
| · Viscosity: | |
| · Kinematic viscosity | Not determined. |
| · Dynamic: | Not determined. |
| · Solubility | |
| · water: | Not miscible or difficult to mix. |
| · Partition coefficient n-octanol/water (log value) | Not determined. |
| · Vapour pressure at 20 °C (68 °F): | 4000 hPa (3000.2 mm Hg) |
| · Density and/or relative density | |
| · Density at 20 °C (68 °F): | 0.8 g/cm ³ (6.7 lbs/gal) |
| · Relative density | Not determined. |
| · Vapour density | Not determined. |
| 9.2 Other information | |
| · Appearance: | |
| · Form: | Aerosol |
| · Important information on protection of health and environment, and on safety. | |
| · Explosive properties: | Not determined. |
| · Solvent content: | |
| · Organic solvents: | 88.8 % |
| · VOC (EC) | --- |
| | 692.6 g/l |
| · VOC-EU% | 88.80 % |
| · Solids content: | 10.4 % |
| · Change in condition | |
| · Evaporation rate | Not applicable. |
| Information with regard to physical hazard classes | |
| · Explosives | Void |
| · Flammable gases | Void |
| · Aerosols | Extremely flammable aerosol. Pressurised container: May burst if heated. |
| · Oxidising gases | Void |
| · Gases under pressure | Void |
| · Flammable liquids | Void |
| · Flammable solids | Void |
| · Self-reactive substances and mixtures | Void |
| · Pyrophoric liquids | Void |
| · Pyrophoric solids | Void |
| · Self-heating substances and mixtures | Void |
| · Substances and mixtures, which emit flammable gases in contact with water | Void |
| · Oxidising liquids | Void |
| · Oxidising solids | Void |

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.06.2022

Version number 3 (replaces version 2)

Revision: 30.03.2022

Trade name: MOTIP HYBRID COLORS SILVER GREY RAL 7001 400 ML

(Contd. of page 6)

- | | |
|----------------------------------|------|
| · Organic peroxides | Void |
| · Corrosive to metals | Void |
| · Desensitised explosives | Void |

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity**

- **LD/LC50 values relevant for classification:**

67-64-1 acetone

| | | |
|------------|-----------|-----------------------|
| Oral | LD50 | 5800 mg/kg (rat) |
| Dermal | LD50 | >15800 mg/kg (rabbit) |
| Inhalative | LC50 / 4h | 76 mg/l (rat) |

111-76-2 2-butoxyethanol

| | | |
|------|------|------------------|
| Oral | LD50 | 1200 mg/kg (ATE) |
|------|------|------------------|

67-63-0 propan-2-ol

| | | |
|------------|------|----------------------|
| Oral | LD50 | 5840 mg/kg (rat) |
| Dermal | LD50 | 13900 mg/kg (rabbit) |
| Inhalative | LC50 | >25 mg/l (rat) |
| | | LC 50: 6h |

108-65-6 2-methoxy-1-methylethyl acetate

| | | |
|------------|------------|----------------------|
| Oral | LD50 | 8530 mg/kg (rat) |
| Dermal | LD50 | >5000 mg/kg (rabbit) |
| Inhalative | LC50 / 4 h | >10000 mg/m3 (rat) |

- **Skin corrosion/irritation** No irritant effect.
- **Serious eye damage/irritation** Causes serious eye irritation.
- **Respiratory or skin sensitisation** No sensitising effects known.
- **STOT-single exposure** May cause drowsiness or dizziness.
- **11.2 Information on other hazards**

- **Endocrine disrupting properties**

None of the ingredients is listed.

SECTION 12: Ecological information

- **12.1 Toxicity**

- **Aquatic toxicity:**

115-10-6 dimethyl ether

| | |
|-------------|------------------|
| EC50 / 96 h | 155 mg/l (algae) |
|-------------|------------------|

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.06.2022

Version number 3 (replaces version 2)

Revision: 30.03.2022

Trade name: MOTIP HYBRID COLORS SILVER GREY RAL 7001 400 ML

(Contd. of page 7)

| | |
|---|--|
| LC50 / 48 h | >4000 mg/l (daphnia magna) |
| LC50 / 96 h | >4000 mg/l (fish) |
| 67-64-1 acetone | |
| LC50/96h | 8300 mg/l (fish) |
| EC50/96h | 7200 mg/l (algae) |
| LC50 / 48 h | 8450 mg/l (crustacean (water flea)) |
| 111-76-2 2-butoxyethanol | |
| LC50 / 48 h | 1550 mg/l (daphnia magna) |
| LC50 / 72 h | 1840 mg/l (Pseudokirchneriella subcapitata) |
| LC50 / 96 h | 1474 mg/l (Regenbogenforelle) |
| 67-63-0 propan-2-ol | |
| LC50/96h | 9640 mg/l (pimephales promelas; 96h) |
| LC50 / 24 h | 9714 mg/l (daphnia magna) |
| 108-65-6 2-methoxy-1-methylethyl acetate | |
| EC50 / 48 h | >500 mg/l (daphnia magna) |
| LC50 / 96 h | 100-180 mg/l (oncorhynchus mykiss / Regenbogenforelle) |

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties**
The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:**
Disposal must be made according to official regulations.
Disposal must be made according to official regulations.

SECTION 14: Transport information

- | | |
|---------------------------------------|---------------------|
| · 14.1 UN number or ID number | |
| · ADR, IMDG, IATA | UN1950 |
| · 14.2 UN proper shipping name | |
| · ADR | 1950 AEROSOLS |
| · IMDG | AEROSOLS |
| · IATA | AEROSOLS, flammable |

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 09.06.2022

Version number 3 (replaces version 2)

Revision: 30.03.2022

Trade name: MOTIP HYBRID COLORS SILVER GREY RAL 7001 400 ML

(Contd. of page 8)

· 14.3 Transport hazard class(es)

· ADR



· Class 2.1F Gases.
· Label 2.1

· IMDG, IATA



· Class 2.1 Gases.
· Label 2.1

· 14.4 Packing group

· ADR, IMDG, IATA not regulated

· 14.5 Environmental hazards:

Not applicable.

· 14.6 Special precautions for user

Warning: Gases.

· Hazard identification number (Kemler code):

-

· EMS Number:

F-D,S-U

· Stowage Code

SW1 Protected from sources of heat.
SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
SG69 For AEROSOLS with a maximum capacity of 1 litre:
Segregation as for class 9. Stow "separated from" class 1 except for division 1.4.
For AEROSOLS with a capacity above 1 litre:
Segregation as for the appropriate subdivision of class 2.
For WASTE AEROSOLS:
Segregation as for the appropriate subdivision of class 2.

· Segregation Code

· 14.7 Maritime transport in bulk according to IMO instruments

Not applicable.

· Transport/Additional information:

· ADR

· Limited quantities (LQ)

1L

· Excepted quantities (EQ)

Code: E0

Not permitted as Excepted Quantity

· Transport category

2

· Tunnel restriction code

D

· IMDG

· Limited quantities (LQ)

1L

· Excepted quantities (EQ)

Code: E0

Not permitted as Excepted Quantity

(Contd. on page 10)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 09.06.2022

Version number 3 (replaces version 2)

Revision: 30.03.2022

Trade name: MOTIP HYBRID COLORS SILVER GREY RAL 7001 400 ML

(Contd. of page 9)

· **UN "Model Regulation":** UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category P3a** FLAMMABLE AEROSOLS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **National regulations:**
- **Other regulations, limitations and prohibitive regulations**

· **Substances of very high concern (SVHC) according to REACH, Article 57**

None of the ingredients is listed.

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H201 Explosive; mass explosion hazard.
- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H302 Harmful if swallowed.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H336 May cause drowsiness or dizziness.
- H351 Suspected of causing cancer.
- EUH066 Repeated exposure may cause skin dryness or cracking.

· **Department issuing SDS:** R&D legislation and regulatory advisor

· **Contact:** e-mail: sds-nl@european-aerosols.com

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 VOC: Volatile Organic Compounds (USA, EU)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 SVHC: Substances of Very High Concern
 vPvB: very Persistent and very Bioaccumulative
 Expl. 1.1: Explosives – Division 1.1
 Flam. Gas 1A: Flammable gases – Category 1A
 Aerosol 1: Aerosols – Category 1
 Press. Gas (Comp.): Gases under pressure – Compressed gas
 Flam. Liq. 2: Flammable liquids – Category 2
 Flam. Liq. 3: Flammable liquids – Category 3

(Contd. on page 11)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 09.06.2022

Version number 3 (replaces version 2)

Revision: 30.03.2022

Trade name: MOTIP HYBRID COLORS SILVER GREY RAL 7001 400 ML

(Contd. of page 10)

*Acute Tox. 4: Acute toxicity – Category 4**Skin Irrit. 2: Skin corrosion/irritation – Category 2**Eye Irrit. 2: Serious eye damage/eye irritation – Category 2**Carc. 2: Carcinogenicity – Category 2**STOT SE 3: Specific target organ toxicity (single exposure) – Category 3***. * Data compared to the previous version altered.**

GB