

## MOTIP RAL Industrial Spray Filler

Ord.-no.: 07303

## Technical Information



Fast drying spray filler with excellent filling properties and coverage for professional use. To fill small irregularities in surfaces, treated and untreated, of wood, metal and aluminium. Spray filler has excellent adhesion and is rust preventive. MOTIP Industrial Spray Filler is easy to sand, both wet and dry (from grain 400).

### Quality & properties

- Fast drying
- Excellent filling property and coverage
- Easy to sand, both wet and dry (from grain 400)
- Corrosion preventive
- Excellent adhesion

### Physical & chemical data

- Base: Acrylic resin
- Colourname: Beige Grey
- Degree of gloss: mat, 10 ±2 GU
- Efficiency: 500 ML – 1,5 - 2 m<sup>2</sup>
- Dry to touch: 10 - 20 min
- Dust dry: 5 - 10 min
- Completely dry: 120 min
- Overcoatable: 120 min
- Surfaces: wood, metal and aluminium
- Minimum Working Temperature: 15 °C
- Maximum Working Temperature: 25 °C
- Vapour pressure: 3500/20
- Flash point: n.a.
- Temperature Resistance: Beige Grey – 110 °C
- Storage stability: 10 years
- Content: 500 ML

### How to use

- Before use, carefully read the directions on the packaging and act accordingly.
- The surface should be clean, dry and free of grease. Remove loose old lacquer and rust and sand the surface.
- The surface should be clean, dry and free of grease. The aerosol should have room temperature. Best processing temperature 15 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimetre.
- Apply the spray filler in several thin layers. Before applying the next layer, again shake the aerosol. After hardening sand, either wet or dry (grain 400). Before applying a finishing coat, apply a primer.
- After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).
- The drying time depends on the ambient temperature, the humidity of the air and the thickness of the lacquer applied.

### Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

### Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

### Marking/Labeling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

For any further technical questions call our hotline +31 (0) 561 69 44 55 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

European Aerosols GmbH, Kurt-Vogelsang-Straße 6, 74855 Haßmersheim - [info-de\(at\)european-aerosols.com](mailto:info-de@european-aerosols.com)  
European Aerosols B.V., Wolframweg 2, NL-8471 XC Wolvega - [info-nl\(at\)european-aerosols.com](mailto:info-nl@european-aerosols.com)