

MOTIP RAL Industrial Zinc Repair Spray

Ord.-no.: 07304



Technical Information

Fast drying zinc spray with good filling properties and excellent adhesion for professional use. To treat galvanised and untreated steel. Zinc spray has outstanding cathodic corrosion prevention, is spot-weldable and is resistant to petrol, chemicals and weather influences. MOTIP Industrial Zinc Spray is heat resistant to 350°C.

Quality & properties

- Fast drying
- Good coverage
- Non-fading and UV resistant
- Good surface hardness
- Resistant to petrol, chemicals and weather influences
- Wear resistant and scratch free
- Excellent adhesion

Physical & chemical data

- Base: Nitrocombi resin
- Colourname: Silver
- Efficiency: 500 ML – 1,5 - 2 m²
- Dry to touch: 10 - 20 min
- Dust dry: 5 - 10 min
- Completely dry: 120 min
- Overcoatable: 120 min
- Surfaces: steel galvanised by immersion
- Minimum Working Temperature: 15 °C
- Maximum Working Temperature: 25 °C
- Vapour pressure: 3500/20 bar
- Flash point: n.a.
- Temperature Resistance: Silver – 110 °C
- Content: 500 ML

How to use

- Before use, carefully read the directions on the packaging and act accordingly.
- The surface should be clean, dry and free of grease.
- The aerosol should have room temperature. Best processing temperature 15 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimetre.
- Apply the zinc repair spray in several thin layers. Before applying the next layer, again shake the aerosol.
- After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).
- The drying time depends on the ambient temperature, the humidity of the air and the thickness of the lacquer applied.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labeling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

For any further technical questions call our hotline +31 (0) 561 69 44 55 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

As of November 24, 2021 – This release replaces all eventually earlier issued versions.

