

MOTIP Tar Spray

Ord.-no.: 090308

Technical Information



Prevent wear and sticking of screw connections exposed to heavy loads such as agricultural vehicles, industrial machines, lorries and off-road vehicles with MOTIP Tar Spray. Tar Spray gives lasting protection, is water-repellent and resistant to the weather and weak acids and bases. MOTIP Tar Spray has excellent adhesion and excellent corrosion prevention.

Quality & properties

- Excellent corrosion prevention
- Water-repellent
- Lasting protection
- Prevents wear and sticking
- Resistant to weak acids and bases
- Excellent adhesion
- Resistant to weather influences
- Directed jetspray
- 360° valve

Physical & chemical data

- Base: Pine tar
- Colourname: transparent brown
- Smell: Characteristic
- Surfaces: Agricultural machinery, Industrial machinery, Truck, Off the road vehicle
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Spray rate: 1 – 1,5
- Vapour pressure: 3500/20 bar
- Relative density: 0.76 g/ml
- Storage stability: 10 y
- Content: 500 ML

How to use

- Before use, carefully read the directions on the packaging and act accordingly.
- The aerosol should have room temperature.
- Best processing temperature 10 to 25°C.
- Before use, shake the aerosol.
- Spray parts to be treated prior to assembly. After evaporation a protective film remains, which simplifies the future disassembly.
- The protective film can be removed with MOTIP Industrial Cleaner.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labeling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

For any further technical questions call our hotline +31 (0) 561 69 44 00 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

As of June 10, 2022 – This release replaces all eventually earlier issued versions.