

## MOTIP Backlight Remover

Ord.-no.: 00164

### Technical Information



Spray, with high dissolving properties, to remove transparent lacquer from backlights. MOTIP Backlight Remover is easy to apply and does not harm the backlights.

#### Quality & properties

- Easy to apply
- Does not harm the backlights
- High dissolving properties
- Not suitable to treat surfaces of polycarbonate

#### Physical & chemical data

- Base: Organic solvents
- Colourname: transparent
- Smell: Characteristic
- Efficiency: 150 ML – 2 to 4 backlights
- Dust dry: 10 - 20 min
- Surfaces: Backlights
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Vapour pressure: 8300/20 bar
- Relative density: 0.73 g/ml
- Storage stability: 10 y
- Content: 150 ML

#### How to use

- Before use, carefully read the directions on the packaging and act accordingly.
- The aerosol should have room temperature. Best processing temperature 10 to 25°C.
- Before use, shake the aerosol.
- Distance to the surface to be treated approximately 10 to 15 centimetre.
- Protect lacquered parts.
- Apply the Backlight Remover generously.
- Remove the lacquer with a dry, non fluffy cloth.

#### Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

#### Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

#### Marking/Labeling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

For any further technical questions call our hotline +31 (0) 561 69 44 00 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

As of August 18, 2022 – This release replaces all eventually earlier issued versions.