

MOTIP Food Grade - Vaseline

Ord.-no.: 005010

Technical Information



Viscous lubricant and preservative. Vaseline can be processed as grease with the lubricating properties of oil. In view of the unique formula, suitable for use in the food industry, in accordance with NSF registration H1, number 139225.

Quality & properties

- NSF registration H1, number 139225
- Water-repellent
- Excellent adhesion
- Prevents wear and sticking
- Resistant to weather influences
- Resistant to salt water, weak acids and bases
- Excellent corrosion prevention
- Misty spray pattern
- 360° valve

Physical & chemical data

- Base: Vaseline
- Colourname: no colour
- Vapour pressure: 3500/20 bar
- Content: 500 ML

How to use

- Before use, carefully read the directions on the packaging and act accordingly.
- The aerosol should have room temperature.
- Best processing temperature 10 to 25°C.
- Before use, shake the aerosol.
- Apply the vaseline in a thin layer.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

For any further technical questions call our hotline +31 (0) 561 69 44 00 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

As of August 18, 2022 – This release replaces all eventually earlier issued versions.