

## MOTIP Cut & Drill Lubricant (Drums)

Ord.-no.: V05583



### Technical Information

Prevent overheating of metals in cutting and drilling activities with MOTIP Cut & Drill Lubricant. Cut and drill lubricant protects and lubricates the tool and reduces wear of the tool. MOTIP Cut and Drill Lubricant is silicone-free and non-corrosive.

#### Quality & properties

- Protects and lubricates the tool
- Reduces wear of the tool
- Silicone-free
- Non-corrosive

#### Physical & chemical data

- Base: Mineral oil
- Colourname: transparent light brown
- Smell: characteristic
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Vapour pressure: 0,6/20 bar
- Flash point: 62 °C
- Relative density: 0.86 g/ml
- Content: 5 l

#### How to use

##### Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

##### Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

##### Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

For any further technical questions call our hotline +31 (0) 561 69 44 00 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

As of November 29, 2021 – This release replaces all eventually earlier issued versions.

European Aerosols GmbH, Kurt-Vogelsang-Straße 6, 74855 Haßmersheim - [info-de@european-aerosols.com](mailto:info-de@european-aerosols.com)  
European Aerosols B.V., Wolfraamweg 2, NL-8471 XC Wolvega - [info-nl@european-aerosols.com](mailto:info-nl@european-aerosols.com)