

MOTIP Copper Spray (Drums)

Ord.-no.: V05561

Technical Information



Prevent wear and sticking of screw connections exposed to very high temperatures with MOTIP Copper Grease. Copper Grease has high thermal stability, is corrosion preventive and resistant to temperatures of -40°C up to + 1.100°C.

Quality & properties

- Simplifies the future removal
- High thermal stability
- Resistant to chemicals and weather influences
- Prevents wear and sticking
- Corrosion preventive

Physical & chemical data

- Base: EP-2 Grease with copper
- Colourname: transparent
- Vapour pressure: 573/20 bar
- Flash point: -40 °C
- Content: 5,00 L

How to use

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

For any further technical questions call our hotline +31 (0) 561 69 44 00 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

As of November 29, 2021 – This release replaces all eventually earlier issued versions.

European Aerosols GmbH, Kurt-Vogelsang-Straße 6, 74855 Haßmersheim - info-de@european-aerosols.com
European Aerosols B.V., Wolfraamweg 2, NL-8471 XC Wolvega - info-nl@european-aerosols.com