

MOTIP Effect Stain Sealer

Ord.-no.: 302901

Technical Information



Fast drying primer on basis of acrylic resin, with excellent isolating properties for interior use. To cut off stains on mineral surfaces (plaster) and in surfaces of wood and concrete. Re-sprayable with all emulsion lacquers, alkyd and waterbased acrylic lacquers. Deco Effect Stain Sealer has excellent adhesion and is non-yellowing.

Quality & properties

- Fast drying
- Excellent adhesion
- Non yellowing

Physical & chemical data

- Vapour pressure: 3500/20 bar
- Flash point: n.a. °C
- Content: 0.2221

How to use

- The surface should be clean, dry and free of grease. When desired, slightly sand the surface, grain 600.
- The surface should be clean, dry and free of grease. The aerosol should have room temperature. Best processing temperature 10 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimetre.
- Apply the lacquer in several thin layers. Before applying the next layer, again shake the aerosol.
- After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).
- The drying time depends on the ambient temperature, the humidity of the air and the thickness of the lacquer applied.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

For any further technical questions call our hotline +31 (0) 561 69 44 00 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

As of November 29, 2021 – This release replaces all eventually earlier issued versions.