

MOTIP Effect Zinc

Ord.-no.: 302801

Technical Information



Fast drying zinc spray with good filling properties and excellent adhesion to treat galvanised and untreated steel. Zinc spray has outstanding cathodic corrosion prevention and is spot-weldable. Deco Effect Zinc Spray is resistant to petrol, chemicals and weather influences and is heat resistant to 350°C.

Quality & properties

- Excellent coverage
- Fast drying
- Heat resistant to 350°C.
- corrosion prevention

Physical & chemical data

- Vapour pressure: 4000/20 bar
- Flash point: n.a. °C
- Content: 0.255

How to use

- The surface should be clean, dry and free of grease. Slightly sand the surface (grain 600).
- The aerosol should have room temperature. Best processing temperature 10 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimetre.
- Apply the lacquer in several thin layers. Before applying the next layer, again shake the aerosol.
- After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).
- The drying time depends on the ambient temperature, the humidity of the air and the thickness of the lacquer applied.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

For any further technical questions call our hotline +31 (0) 561 69 44 00 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

As of November 29, 2021 – This release replaces all eventually earlier issued versions.

European Aerosols GmbH, Kurt-Vogelsang-Straße 6, 74855 Haßmersheim - info-de@european-aerosols.com
European Aerosols B.V., Wolfraamweg 2, NL-8471 XC Wolvega - info-nl@european-aerosols.com