

MOTIP Shock Oil

Ord.-no.: 090305

Technical Information



Loosen rusted parts with MOTIP Shock Oil. As a result of the fierce decrease in temperature to -30°C and the lubricating properties of shock oil, the screwed connection can be loosened.

Quality & properties

- Briefly decreases the temperature to -30°C
- Excellent lubricating properties
- Very effective
- Directed jetspray

Physical & chemical data

- Base: Aliphatic hydrocarbons
- Colourname: transparent light brown
- Smell: Vanilla
- Surfaces: Screwed connections, Fasteners (screws, bolts and nuts)
- Minimum Working Temperature: 10°C
- Maximum Working Temperature: 25°C
- Spray rate: 1,92
- Vapour pressure: 3500/20 bar
- Relative density: 0.65 g/ml
- Storage stability: 10 y
- Content: 500 ML

How to use

- Before use, carefully read the directions on the packaging and act accordingly.
- The aerosol should have room temperature.
- Best processing temperature 10 to 25°C .
- Before use, shake the aerosol.
- Spray the screwed connection for some seconds, by briefly pressing the nozzle several times.
- As a result of the fierce decrease in temperature and the lubricating properties of shock oil, the screwed connection can be loosened.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labeling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

For any further technical questions call our hotline +31 (0) 561 69 44 00 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

As of June 10, 2022 – This release replaces all eventually earlier issued versions.