

## MOTIP Effect Fluor

## Technical Information



Decorative, fluorescent lacquer with excellent adhesion to treat surfaces, treated and untreated, of metal, stone, wood, glass and various types of plastic. For an optimum result, apply a base layer of MoTip Deco Effect white primer. MoTip Deco Effect Fluorescent Lacquer is available in 4 colours, red-orange, pink, yellow and green.

**Ord.-no:** 302301, 302302, 302303, 302304

---

### Quality & properties

Excellent coverage  
Fast drying  
Fluorescent

---

### Physical & chemical data

Base: Nitrocombi resin

Colourname:

- red-orange
- pink
- yellow
- green

Efficiency: 400 ML – 1,25 - 1,75 m<sup>2</sup>

Dust dry:

- 5 - 10 min
- 5 min

Dry to touch: 10 - 20 min

Completely dry: 120 min

Overcoatable: 120 min

Surfaces: metal, concrete, stone, wood, glass and various types of plastic

Minimum Working Temperature: 15 °C

Maximum Working Temperature: 25 °C

Flash point: n.a.

Temperature resistance: 110 °C

Content: 400 ML

---

**How to use**

The surface should be clean, dry and free of grease. Slightly sand the surface (grain 600).

The aerosol should have room temperature. Best processing temperature 10 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimetre.

Apply the lacquer in several thin layers. Before applying the next layer, again shake the aerosol.

After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).

The drying time depends on the ambient temperature, the humidity of the air and the thickness of the lacquer applied.

**Environmentally sound**

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

**Disposal**

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

**Marking/Labelling**

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

**As of August 4, 2025** – This release replaces all eventually earlier issued versions.