

MOTIP Seam Sealant

Technical Information



Seal joints, edge-to-edge joints, grooves and overlapping in car, carriage and container construction with MOTIP Seam Sealant. Particularly useful for sealing welding points at the front and rear of cars and at places which are difficult to reach in the boot and interior of the vehicle. Properties: As it is very stable and processed almost fibre-free, MOTIP brushable sealant has an almost true-to-original surface structure. The sealant has excellent adhesive properties on untreated, primed, painted and galvanized metal sheets. The sealant dries swiftly, enabling it to be painted over quickly with all paints normally available. The sealant can stand temperatures from -25°C to +80°C.

Ord.-no: 07505

Quality & properties

Physical & chemical data

Base: Synthetic resin
Colourname: grey
Surfaces: For sealing of joints, edge-to-edge joints, grooves and overlapping in car, carriage and container construction.
Minimum Working Temperature: 10 °C
Maximum Working Temperature: 25 °C
Content: 750 ml

How to use

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of August 4, 2025 – This release replaces all eventually earlier issued versions.