

MOTIP Wood Marking

Ord.-no.: look at ordering information

Technical Information



Fast drying marking spray with high coverage, to apply markings on wood, both wet and dry. Wood marking spray is resistant to weather influences and has a directed jetspray in order to properly apply characters.

Quality & properties

- Very high coverage
- Resistant to weather influences
- Excellent adhesion
- Bright colours
- Directed spray to enable the application of signs
- Fast drying

Physical & chemical data

- Base: Acrylic resin
- Colourname:
 - ◊ blue
 - ◊ red
 - ◊ white
 - ◊ orange
- Smell: Characteristic
- Content: 500 ML

How to use

- Before use, carefully read the directions on the packaging and act accordingly.
- Best processing temperature 10 to 25°C
- Before use, shake the aerosol for 2 minutes.
- Apply the wood marking spray
- After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).
- The drying time depends on the ambient temperature, the humidity of the air and the thickness of the lacquer applied.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labeling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

For any further technical questions call our hotline +31 (0) 561 69 44 00 from Monday to Thursday from 9 h a.m. to 3 h p.m. or on Friday until 12 h p.m.

As of August 18, 2022 – This release replaces all eventually earlier issued versions.