



<b>Product name</b>	:	<b>MoTip Deco Effect Frigo White</b>
<b>Article number</b>	:	<b>303202</b>
<b>Supplier / Producer</b>	:	<b>MOTIP DUPLI B.V.</b>
		<b>Wolframweg 2</b>
		<b>NL-8471 XC WOLVEGA</b>
		<b>Telephone number</b> +31 561 – 69 44 00
		<b>Telefax number</b> +31 561 – 69 44 31

---

## Product description

High quality lacquer to repair small damage to kitchen equipment.

## Product characteristics

Excellent coverage and filling property  
Lasting colour and lasting gloss  
Scratch free and shock proof  
Resistant to chemicals  
Corrosion preventive  
Good adhesion

## Physical and Chemical Characteristics

Contents	:	400 ml
Base	:	Alkyd resin
Colour	:	White
VOC-content	:	Approximately 85% w/w
Solid content	:	Approximately 15% w/w
Gloss	:	High gloss 90 at an angle of 60°
Coverage	:	1,25 to 1,75 m <sup>2</sup>
Dust dry	:	After 30 to 60 minutes
Tack free	:	After 3 to 4 hours
Hardened/re-sprayable	:	After 24 hours
Heat resistant	:	To 110°C

## Usage

**Before use, carefully read the directions on the packaging and act accordingly.**

### Pre Treatment

The surface should be clean, dry and free of grease. Remove loose old lacquer and rust and sand the surface. Apply a layer of MoTip Deco Effect primer suitable for the surface. After drying, sand the base layer (grain 600).

### Treatment

The surface should be clean, dry and free of grease. The aerosol should have room temperature. Best processing temperature 15 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimetre.

Apply the lacquer in several thin layers. Before applying the next layer, again shake the aerosol.

**Even when the lacquer has hardened, do not treat with acrylic lacquer or nitro-cellulose lacquer.**

After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).

**The drying time depends on the ambient temperature, the humidity of the air and the thickness of the lacquer applied.**